



»»» FULLY SYNTHETIC MOTOR OIL

A universal synthetic motor oil, developed according to the most recent technology and based on specially selected base oils with a high natural viscosity index. With the addition of a well-balanced choice of advanced additives the following properties are obtained:

- a high and very stable viscosity index
- a high resistance against shearing
- a very fast cold start
- a safe lubrication film at very high temperatures
- reduced formation of combustion ashes
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

»»» APPLICATIONS

This universal synthetic motor oil is suitable for use in petrol and diesel engines, with or without turbo-charging. This product meets the requirements of several OEM's and thus has a wide application.

»»» PERFORMANCE LEVEL

- ACEA: C3
- API: SN/CF
- BMW: LL-04
- GM: DEXOS 2
- MB: 229.31/229.51

»»» CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.840
Viscosity 40 °C	mm ² /s	70.70
Viscosity 100 °C	mm ² /s	13.10
Viscosity Index		189
Flash Point COC	°C	224
Pour Point	°C	-51
Total Base Number	mgKOH/g	7.7
Sulphate Ash	%	0.80
Viscosity -35 °C	mPas	5380

»»» PACKAGING

